

TELECOMUNICACIONES AGM TELECOMMUNICATIONS AGM



Características

Facilidad de instalación

Terminales de acceso frontal que facilitan la instalación e incrementan la seguridad del personal técnico en la instalación, puesta en marcha y mantenimiento.

Excelente comportamiento en flotación

Diseñadas para 12 años de vida útil a 25°C con placas resistentes a la oxidación. Disponibles versiones HT (Alta Temperatura) con doce años de vida útil a 35°C, ver tabla.

Aplicaciones

Sistemas de comunicaciones, estaciones de microondas, estaciones móviles, centros de datos, SAI, etc.

Main features

Longer design life

Front access terminals for easier installation and increasing technical staff security during installation, commissioning and maintenance.

Excellent performance in standby use

Designed for 12 years of service life at 25°C and with oxidation resistant plates. Also available HT models (High Temperature) with 12 years of service life at 35°C, see table below.

Main uses

Telecommunications systems, microwave stations, mobile stations, data centers, UPS, etc.

Model	Nominal Voltage (V)	Rated Capacity (AH) 10HR	Approx Dimension								Approx Weight kg	I.R.	Terminal type
			Length		Width		Height		Total Height				
			mm	in.	mm	in.	mm	in.	mm	in.			
UP-TF65-12	12	70	395	15.55	105	4.13	255	10.4	255	10.4	22.5	7.7	1+1 FA
UP-TF80-12	12	82	395	15.55	105	4.13	255	10.4	255	10.4	24.5	6.4	1+1 FA
UP-TF92-12	12	92	395	15.55	105	4.13	286	11.3	286	11.3	27.5	5.5	1+1 FA
UP-TF100-12	12	100	398	15.67	110	4.33	286	11.26	286	11.26	33.0	6.55	1+1 FA
UP-TF110-12	12	109	510	20.1	110	4.33	235	9.3	235	9.3	33.0	5.84	1+1 FA
UP-TF130-12	12	136	555	21.8	125	4.9	324	12.8	324	12.8	50.5	5.1	1+1 FA
UP-TF150-12	12	152	555	21.8	125	4.9	320	12.6	320	12.6	51.2	4.85	1+1 FA
UP-TFH150-12	12	152	555	21.8	125	4.9	320	12.6	320	12.6	52.8	4.85	1+1 FA
UP-TFH155-12	12	152	555	21.8	125	4.9	280	11.0	280	11.0	50.5	4.42	1+1 FA
UP-TF180-12	12	180	555	21.8	125	4.9	320	12.6	320	12.6	57.3	4.03	1+1 FA
UP-TF200-12	12	190	555	21.8	125	4.9	320	12.6	320	12.6	59.2	3.95	1+1 FA
UP-R200-6	6	207	386	15.2	168	6.6	232	9.1	232	9.1	35.0	1.4	1+1 FA
UP-R300-4	4	311	386	15.2	168	6.6	232	9.1	232	9.1	36.0	0.81	1+1 FA
UP-R400-2	2	414	386	15.2	168	6.6	232	9.1	232	9.1	28.5	0.39	1+1 FA
UP-R500-2	2	518	386	15.2	168	6.6	232	9.1	232	9.1	32.0	0.35	1+1 FA
UP-R600-2	2	621	386	15.2	168	6.6	232	9.1	232	9.1	36.0	0.31	1+1 FA
UP-RH500-2	2	466	386	15.2	168	6.6	232	9.1	232	9.1	32.0	0.35	1+1 FA

* Las medidas y especificaciones están sujetas a modificaciones sin previo aviso, para más información póngase en contacto con MASTER BATTERY.

* Technical specifications may be change without any notice, for more information contact MASTER BATTERY.



Serie UP-TELECOM